Capacitive Electromagnetic Flowsensor CX Specifications

Model		CX		
Nominal Diameters		10	15	20
Accuracy-Guaranteed Flow-Rate Range		0.5 ~ 15 L/min	2.0 ~ 60 L/min	
Displayable Flow-Rate Range		0.0 ~ 18 L/min	0.0 ~ 72 L/min	
Low-Flow Cut-Off		0.45 L/min	1.8 L/min	
Repeatability Accuracy		±2%F.S. (No need of straight piping)		
Temperature Characteristics	Ambient Temperature	±5%F.S. (Relative error when changing from the standard temperature 25°C to 10°C or 50°C)		
	Fluid Temperature	±5%F.S. (Relative error when changing from the standard temperature 25°C to 1°C or 85°C)		
Piping Connection		Rc3/8	Rc1/2	Rc3/4
Fluid Temperature Range		0 ~ 85°C		
Conductivity Range		5μS/cm ~ 3mS/cm		
Measurable Fluids		Water, water-soluble coolant		
Working Pressure		0 ~ 1 MPa		
Pressure Resistance		2 MPa		
Pressure Drop		0.02 MPa or less		
Response Time (63% Response)		0.25s ／ 0.5s ／ 1s ／ 2s ／ 5s (Default Value: 1s)		
Working Ambient Temperature/Working Ambient Humidity		0 ~ 50°C ／ 35 ~ 85%RH (Non-condensing)		
LED Display		Main Display: 4 digits and 7 segments (Two-color display in green and red) Sub Display: 6 digits and 11 segments (White)		
	Main Display	Displays either instantaneous flow-rate or accumulated flow volume		
	Sub Display	Output mode or input mode, flow direction, arbitrary characters (Selectable)		
Display Unit		Instantaneous flow-rate: L/min; Accumulated flow volume: L, kL or ML (Selectable)		
Switch Output		NPN or PNP transistor output *Please select when ordering.		
	Maximum Load Voltage/Current	30 VDC / 50 mA		
	Output Modes	Level judgment mode/ Window judgment mode/ Trip accumulated flow volume output mode/ Accumulated flow volume pulse output mode/ Alarm output mode (Selectable) (Accumulated flow volume pulse output mode: Nominal Diameter 10: Pulse unit: 0.01 L/P, ON-time: 10 ± 5 ms ; Nominal Diameter 15 and 20: Pulse unit 0.1 L/P, ON-time: 50 ± 5 ms)		
Analog Output *1	Voltage/ Current	1 to 5 V DC load impedance: 50 kΩ or higher/4 to 20 mA load impedance: 500 Ω or less * Please select when ordering.		
Switch Input *1	Input Time	20 ms or longer		
	Short-Circuit Current	Approximately 2 mA		
Protection Class		IP65 (When using the body-connection connector cable)		
Current Consumption		65 mA or less		
Power Source		24 VDC ± 10% P-P Ripple within ± 10%		
Installation Position		Free		
Weight		Approx. 460 g	Approx. 490 g	Approx. 520 g
Wetted-Parts Materials		PPS / FKM / Bronze (CAC804)		
Accessory		Body-connection connector cable: 3 m		
Optional Parts		Installation bracket		

Note 1. Please read and understand the product specifications before using the product.
Note 2. In case of consideration to arrange plural pieces of the products by the side of a flow rate type filling apparatus in Japan, please refer to Japanese Patent No. 3916032 before deciding to install them.
*1 Please select either analog output or switch input.

Pin assignment for the exclusive body-connection connector cable

Connector Pin Numbers on the Flowsensor Side	Body-connection connector portion Pin arrangement	Connection Cable (4 cores)	Contents
1		Brown	Power (+)
2		White	OUT 2: Analog output (Voltage or Current)
3		Blue	GND
4		Black	Out 1: Switch output

Model Codes

Basic Model	Nominal Diameters	Connection Shape	_	Switch Output	Analog Output	_	Accessory Cable	Option Bracket	Contents
CX									CX
	10								Flow-Rate Range: 0.5 ~ 15 L/min
	15								Flow-Rate Range: 2.0 ~ 60 L/min
	20								
		A							Nominal Diameter 10: Rc 3/8; Nominal Diameter 15: Rc 1/2; Nominal Diameter 20: Rc 3/4
				N					NPN transistor
				P					PNP transistor
					V				1 ~ 5 VDC
					A				4 ~ 20 mADC
							3		Body-connection connector cable: 3 m (standard)
							N		None
								B	Installation bracket
								N	None (standard)

External Dimensions



Unit: mm

Model	10A	15A	20A
L	90	95	
W	40		
H	86.8		

Technical specifications in this catalog are up-to-date as of April 2015.

Aichi tokei denki co., ltd.
1-2-70 Chitose, Atsuta-ku, Nagoya, 456-8691, Japan
URL : http://www.aichitokei.co.jp
For inquires, please contact us.
Overseas Business Division TEL +81-(0)52-661-5150

To Our Customers

Please understand that product specifications may be changed without notice in order to improve performance. We are always happy to provide the latest catalogs and brochures, and respond to inquiries made to our offices.

Revision No. 1.0

OKE-FMO-000-□

Reliability, Creativity, Service

Capacitive Electromagnetic Flowsensor

CX

Resistant to foreign substances

Resistant to deposits

Straight piping is not required

Five "No"s and Five "Can"s

S&S Sensors, Systems & Services

Aichi tokei denki co., ltd.

The CX offers five "No"s for easy operations!

"No" electrodes are exposed to fluids.

The plastic material containing derivatives is used in the flow channel to prevent the electrodes from being exposed to fluids. This made the CX strong against foreign substances and deposits.



2

"No" moving parts

The CX uses the law of electromagnetic induction in its measurement principle. With its no-obstruct structure with no moving parts in the flow channel, it has only little pressure loss with high durability.



1

"No" straight piping required

The rectangle structure is adapted to the flow channel in order to stabilize flows and eliminate straight piping.

The rectangular structure is the key!



3

"No" measures are required against power supply noise

No measures are needed against power supply noise even if an inexpensive switching power supply device is used.
It conforms to the EC Directive and obtained the CE mark.

5

"No" need to have a large installation space

The device can be installed in a small space due to the compact body size without straight piping.

4

Only the CX can offer five "Can"s!

1. Abnormal flow-rates can be identified at a glance.

By setting a level-judgment value to determine abnormal flow-rates, the CX indicates normal flow rates in the green LED light while it automatically changes to indicate abnormal flow rates in the red LED light. Just by looking at the LED indicator, the status of flow-rate monitoring can be checked.

Normal flow-rate Green

An abnormal flow-rate is detected.

Abnormal flow-rate Red

* In these examples, the value to determine abnormal flow rates is set at 12.0 L/min.

2. Multiple units installed can be identified.

Use characters A to Z, 0 to 9, and symbols to set up arbitrary names and numbers.

Up to six characters can be set to name a unit. It is useful to identify the cooling system.



3. The meters can be controlled by external input.

When using the functions of trip flow volume accumulation or zero point adjustment, resetting the accumulated value of trip flow volume or adjusting the zero point by external input signals can be performed.

Trip accumulated flow volume

4. The flow displays can be switched over.

The values of the main and sub displays can be switched over.

5. The flow direction can be changed.

With a simple setting change, the direction of measuring can be reversed.

System Example

Analog Output
1 ~ 5 VDC or 4 ~ 20 mA

Switch Input

PLC, etc.

Control signals

Contact signals

Electric valve

Beacon light

Flow-rate can be controlled if used in combination with electric valves.

Abnormal flows can be visually recognized in combination with the warning of a beacon light.

Abnormal flow-rates can be visually recognized with the light when flow-rates cannot be ensured even with the flow-rate control.

Applications

For die-casting machines, injection molding machines and welding machines



Burrs and shrinkage often cause quality defects.

Weld defects

The flow amount of cooling water is the root cause of such defects!

Monitoring the flow amount of cooling water stabilizes the quality.

For cutting machines and grinding machines



Too much dispersion in the hole sizes

Too many grinding streaks

The flow amount of the coolant is the root cause of such defects!

Monitoring the flow-rate of the coolant stabilizes the quality.