





YOUR TYRE CHANGER OF CHOICE









# HIGH PERFORMANCES EASE OF USE LESS TECHNICIAN'S FATIGUE

monty® 8700 provides a superior set of tools to minimize effort and the damaging risks when working with run-flat and high performance tyres



## **POWERMONT**<sup>IM</sup>

The innovative system to mount & demount tyres

- SAFE: Thin mount / demount finger protects the bead from stress during mounting - Servo assisted movement of the mount /demount tool, the finger follows the rim profile and prevents damages of TPMS and valve - Integral and soft tool protection avoids rim damage
- FAST: Automatic synchronization of all tools positions Fast disengage and repositioning of the mount demount tool - Standalone tool for lower bead mounting
- EASY TO USE: Control of the mount/demount tool's trajectory - Intuitive and simple control of the operations
- RELIABLE: Long lasting mount / demount tool made of steel with integrated plastic protection

### DYNAMIC BEAD BREAKER

The bead breaking of choice for RFT, UHP and low aspect ratio tyres

- Precise and damage free
- Disk position synchronized by servo drive Fast & precise
- Disk pneumatic tilt Optimum performance with sticked beads
- Ergonomic & effortless

### **CENTER POST CLAMP**

The solution choice for light alloy wheels

- No wheel damage
- Does not require jaw protection
- Not restricted by clamping jaw maximum opening
- Faster clamping of UHP and RFT, it does not require use of the bead assist device to insert the jaws between the bead and the rim

### **SMARTSPEED™**

smartSpeed<sup>™</sup> continuously controls the mount/demount conditions in order to provide the optimum torque/speed combination to the motor

- SAFE: always the most appropriate torque to avoid interruption of the process and damages to tyre and rim
- FAST: automatically selects the maximum speed possible up to 20 rpm
- EASY TO USE: smartSpeed™ automatically sets the speed to the torque required

## PNEUMATIC BEAD DEPRESSOR PBD330

The essential tool working with high performance tyres

- PBD330 keeps tyre bead into the wheel drop center for a safe and correct mounting / demounting of tyres with stiff sidewall
- The tool shape is optimized to avoid tool slippage that could damage tyres and wheels
- Tool's rear hook helps lifting heavy tyres

Features	monty® 8700b	monty® 8700g
Clamping range	12" - 30"	12" - 30"
Max tyre width	380 mm	380 mm
Max wheel dimension	47"	47"
smartSpeed™	CW 7 - 20 rpm	CW 7 - 20 rpm
powerMONT™	standard	standard
Bead seater	n.a	standard
Bottom bead viewer	mirror	camera
Wheel lift & Tools storage	option	option

on Equipment s.r.l. · Via Prov. Carpi, 33 · 42015 Correggio (RE

-on Equipment Austria GmbH • Hauptstrasse 24/Top 14 • A-2880 St. Corona/Wechsel (RE) : +43 1 865 97 84 • Fax: +43 1 865 97 84 29 • www.hofmann-equipment.com

on Equipment France · ZA du Vert Galant · 15, rue de la Guivernone BP 97175 uen-l'Aumône - 95056 Cergy-Pontoise CEDEX +33 134 48 58-78 · Fax: +33 134 48 58-70 · www.hofmann-equipment.com

on Equipment s.r.l. • Via Prov. Carpi, 33 • 42015 Correggio (RE) e: +39 0522 733-411 • Fax: +39 0522 733-410 • www.hofmann

ap-on Equipment Ltd. · Unit 17 Denney Road, King's Lynn · Norfolk PE30 4HG one: +44 118 929-6811 · Fax: +44 118 966-4369 · www.hofmann-equipment

