

CARLIFT II 5.0

LIFTING TECHNOLOGY



CARLIFT

VP 251143

Four Post Lift with 5000 kg load capacity

DESCRIPTION:

- ◆ Four post lift with electro-hydraulic drive unit for surface mounting
- ◆ Special runway profile and reinforced crossbeams for high flexural resistance and long-term stability
- ◆ Torsion-free, high-precision fine adjustment of the platforms to the crossbar, resulting in perfect conditioning for wheel alignment
- ◆ Extra reinforcement plates welded onto runways for optimum stability
- ◆ Large runway width for all vehicle track widths
- ◆ Runways equipped with pre-integrated guide rail for axle lift
- ◆ Lowering device for chassis alignment included as standard, with precision-adjustable lock ladder and electromagnetically operated latches
- ◆ Low travel height for easy drive on
- ◆ Emergency DOWN feature in case of power failure
- ◆ Paint: powder coating:
anthracite grey, RAL 7016, (column, crossbar)
gentian blue, RAL 5010 (platform, drive-on ramps)

STANDARD DELIVERY:

- ◆ Four-post lift, Type CARLIFT II 5.0
- ◆ Operating box with control and hydraulic power unit
- ◆ Lockable main switch
- ◆ Settling device for wheel alignment
- ◆ 2 pieces drive-on ramps, 2 pieces roll bar
- ◆ Operating manual and inspection log book
- ◆ EC Declaration of Conformity CE
- ◆ Transport packaging

TECHNICAL DATA:

Load capacity CE	5000 kg
Lifting height max.	1995 mm
Raising / Lowering time (load-dependent) approx.	30 s / 30 s
Drive-on height	175 mm
Drive-on height with setup for wheel alignment	225 mm
Compressed air	8 bar
Inside columns	2900 mm
Motor power	5,5 kW
Fuse gG	16 A
Power supply	3/N/PE 400 V 50 Hz
Dimensions total (L x W)	0 mm x 0 mm
Dimensions runway (L x W)	0 mm x 0 mm
Weight	1650 kg

ACCESSORIES:

VZ 971333	Lighting inside of runways (4 times)
VZ 990390	Lighting (6 lamps) inside of runways
VZ 985059	Hand pump for manual lowering Carlift II 5.0
VZ 971302	Inground set, short flaps (4 pcs.)
VZ 990449	Mains power 3 x 230V CARLIFT NAF
VZ 975617	Compressed-air quick coupler
VZ 975181	Compressed-Air Servicing Unit
VZ 990029	Light barrier s. device to avoid c. with ceiling
VZ 971331	Exit Flaps enable drive over Lift
VZ 971503	Approach Ramps 1,5 m Carlift II
VZ 970112	Wheel-Free Jack 3.5 for Four-Post-Lift
VZ 975069	Plastic chocks set 47 x 132 x 340 mm
VZ 975074	Plug-In Type Hard Rubber Chocks
VZ 970027	Sliding plates long 1465 mm
VZ 975026	Sliding plates 60 mm lateral motion
VZ 975655	Set of compensating plates for turntables, 5.35m
VZ 975656	Set of compensating plates for turntables, 5.35m
VZ 975664	Set of compensating plates for turntables, 5.35m
VZ 975665	Set of compensating plates for turntables, 5.35m
VZ 975657	Compensating Plates, Reinforced (2 pieces)
VZ 975027	Sliding plate covers, standard aluminium
VZ 975709	Covers for Sliding Plates, 4 pieces
VM 999035	Hydraulic Oil (HLP-D 22) per litre
VM 999014	Hydraulic Oil (HLP 32) Biodegradable
VM 995661	Assembly Material for Four-Post Lift
VV 997453	Packing Carlift -overseas-