

### TECHNICAL SPECIFICATIONS

Flow range	1 to 30 l/min (0.25 to 7.5 gal/min)
Maximum working pressure	100 bar (1,425 psi)
Units of measure	Liters, Gallons, Quarts, Pints
Accuracy / Repeatability	±0.5 %
Inlet	1/2" BSP (F)
Outlet	1/2" BSP (F)
Maximum totalizer	999999 units
Maximum recorded dispense	999.9 units
Different preset values in memory	10
Working temperature range	-10 °C to 50 °C (14 °F to 122 °F)
Battery	4 x AA alkaline
Wetted parts	Aluminum, AISI 316 Stainless Steel, Buna-N, Delrin, Brass, Zinc plated steel
Weight (with no outlet)	1,7 kg (3.7 lb)



### ORDER INFORMATION

365 310	Preset Meter, no outlet
365 316	Preset meter, rigid outlet with 1/4 turn non-drip tip
365 317	Preset meter, formable outlet with 1/4 turn non-drip tip



# Pre-set

## Electronic Pre-set Meter



**SAMOA INDUSTRIAL, S. A. - HEADQUARTERS**  
 SPAIN AND EXPORT MARKETS  
 POL. IND. PORCEYO, 1-14 - CAMINO DEL FONTÁN, 831  
 E-33392 GIJÓN (ASTURIAS), SPAIN  
 TEL.: +34 985 381 488 - FAX: +34 985 147 213  
 export@samoaindustrial.com - www.samoaindustrial.com

**SAMOA LTD.**  
 UNITED KINGDOM AND REP. OF IRELAND  
 sales@samoaltd.uk - www.samoaltd.uk

**SAMOA S.A.R.L.**  
 FRANCE  
 samoafrence@samoafrence.com - www.samoafrence.com

**SAMOA-HALLBAUER GMBH**  
 GERMANY AND AUSTRIA  
 info@samoahallbauer.de - www.samoahallbauer.de

**SAMSON CORPORATION**  
 NORTH AMERICA  
 info@samsoncorporation.com - www.samsoncorporation.com

**SAMOA CHINA SALES OFFICE**  
 china@samoaindustrial.com



©Copyright, SAMOA INDUSTRIAL, S.A.

SAMOA Industrial, S.A. is an ISO 9001, ISO 14001 and ISO 45001 certified company.

P-0322 • 1.000 l • Capacitor 33k 350 pF



YouTube

# Electronic Pre-set Meter

- Electronic meter with pre-set function.
- Hands-off operation: meter automatically shuts off once the preset volume is delivered.
- With large LCD display and high flow inlet swivel.
- Works with easy to replace "AA" alkaline batteries.

## Protective TPE shroud

Increased durability.

## Easy and intuitive programming

6-key integrated keypad with large LCD screen.

## Durable cast body

Aluminium die cast for longer life and lighter weight.

## Reliable valve operation

Valve automatically shuts off once the delivered flow reaches the preset volume.

## Easy to operate

Four finger trigger for increased user comfort.

## 1/2" High flow inlet swivel with protective TPE swivel boot

Heavy Duty inlet swivel with inlet filter.



## Two Line LCD

Large character batch display. Smaller character totalizer. Can be programmed to measure in Liters, Pints, Gallons or Quarts.

## Can store up to 10 preset values in memory

Faster operation, simply recall the desired volume.

## Transaction history

Keeps in memory the last 5 transactions, storing time, date and volume delivered.

Larger digits, show batch volume dispensed.

Battery level indicator.

Buttons to set the preset volume.

Preset mode selector.

Units of measure (Liters, Pints, Quarts, Gallons).

Smaller digits. They can show the preset volume, the resettable totalizer (TRIP) or the permanent totalizer.

Two buttons to select the different display modes, select the preset values stored in the meter memory, or view recent display history.



## Fluids Handled

- MOTOR OIL
- HYDRAULIC OIL
- ANTI-FREEZE
- GEAR OIL
- AUTOMATIC TRANSMISSION FLUID

## Easy to replace batteries

Four AA standard alkaline batteries provide the power required for an effective valve operation.

