MixRite Electric Pumps

MixRite E-300

The electric dosing pump by Tefen Flow & Dosing Technologies.

Tefen's MixRite E-300 electric dosing pump directly injects liquid additives into water lines.

The MixRite E-300 operates against water line-pressure of up to 5 Bar.



Main Advantages

- Handles a variety of chemicals with a large range of flow rates
- Input 12VDC, 16 AMP
- Zero pressure loss along the water line
- Can be powered using mains electricity 220 VAC or alternative network power sources, such as car battery and solar panel charged batteries
- Easy to install and operate
- Strong and durable external polycarbonate cover which is waterproof and UV-resistant
- Very low maintenance

Fertilizer Pump - 2 Modes of Operation

Manual operation

- The pump can be operated at the desired level of injection
- Volume scale ranging between 10-100% of the maximum flow rate
- High repetition capabilities, maintaining the same volume until defined otherwise

Automatic option using irrigation controller*

- The pump stops and starts according to operation of input.
- The dosing will be fully proportional



^{*} Irrigation Controller is not included in the kit

Each pump comes with:

- 1. 10m pipe (Ø12mm) with BSPT 1/2" connector
- 2. Input kit
- 3. Output kit with air release valve & check valve

Simple and Low Cost Installation



Average Injection Flow Rate

	МТу	ре									
Flow LPH	350										
	300										
ᇤ	250									/	
	200										
	150							/			
	100			//		/					
	50										
	0	10	20	30	40	50	60	70	80	90	100
									P	ump '	Value
		<u> </u>	Bar	_	3 Bar	_	— 5 Ba	r			

M Type – L/H									
Pump value	2 bar	4 bar	5 bar						
10	21								
20	49	32							
30	86	64	39						
40	120	94	71						
50	153	125	98						
60	181	151	129						
70	205	168	150						
80	236	191	186						
90	266	234	214						
100	301	256	252						

Two Models





ctefen

Tefen Flow & Dosing Technologies Ltd.

Kibbutz Nahsholim, 3081500 Israel | Tel. 972 4 6395554 | info@tefentech.com | tefentech.com

For the removal of any doubt, this documents does not constitute an offer on the part of Tefen and/or any undertaking on its part. Tefen may change the content of this document and/or the technical specifications of the products and/or add and/or remove products and/orchange prices and/or any terms and conditions specified in this document at any time and upon its sole discretion without any prior notice.