


# oxi::lyser™

oxi::lyser™ monitors dissolved oxygen & temperature

- s::can plug & measure
- measuring principle: optical / fluorescence
- multiparameter sensor
- ideal for surface water, ground water, drinking water and waste water
- long term stable and maintenance free in operation
- factory precalibrated
- automatic cleaning with compressed air
- mounting and measurement directly in the media (InSitu) or in a flow cell
- no flow necessary
- operation via s::can terminals & s::can software
- minimal maintenance (no consumables)



recommended accessories	
part number	article name
D-330-xxx	con::cube V3
D-320-xxx	con::lyte
B-44	cleaning valve
B-44-2	
C-210-sensor	10 m extension cable for s::can physical probes and s::can ISE probes
F-11-oxi-ammo	carrier oxi::lyser / soli::lyser / s::can ISE probes
F-48-oxi	oxi::lyser or soli::lyser flow-cell (by-pass setup), PVC

### technical specification

measuring principle	fluorescence	housing material	CPVC, stainless steel, epoxy
resolution	0.01 mg/l O <sub>2</sub>	weight (min.)	540 g
accuracy (standard solution)	O <sub>2</sub> : +/- 0.02 mg/l or +/- 1 %* (*whichever is greater)	dimensions (Ø x l)	50.5 mm x 132 mm
response time (T90)	60 ... 0 sec.	operating temperature	0 ... 60 °C
reference standard	saturated sodium sulfite solution	operating pressure	0 ... 7 bar
integrated temperature sensor	0 ... 50 °C	installation / mounting	submersed or in a flow cell
resolution temperature sensor	0.2 °C	process connection	R 1 1/2"
integration via	con::cube con::lyte con::nect	pH range	2 ... 10
power supply	6 ... 16 VDC	ingress protection class	IP68
power consumption (max.)	0.32 W	automatic cleaning	media: compressed air permissible pressure: 2 ... 4.5 bar
interface to s::can terminals	sys plug (IP67), RS485	storage temperature	0 ... 60 °C
cable length	10 m	conformity - EMC	EN 50081-2, EN55011
		conformity - safety	EN 61000-4, EN61010-1
		extended warranty (optional)	3 years

### measuring range

		parameter		part number
		O <sub>2</sub> [mg/l]	temperature [°C]	
oxi::lyser (O <sub>2</sub> , temp)	min.	0	0	E-501-075
	max.	25	50	